

## Description

**Part Number: SW2390**

### Features:

- T304 16GA Stainless Steel Construction
- Single 3Ø, 30A 480V & Single 3Ø, 60A 480V IP67/69, 4/4X Mechanical Interlock with On/Off LED. UL Listed.
- 20A, 125V black weather resistant duplex GFCI with extra duty non metallic rain-tight in use cover
- Removable lid and rear access panel
- Pre-drilled mounting holes and access cutout for underground conduit entry in base
- Pre-installed watertight conduit hub. No Drilling!
- 21”L x 13.0”D x 48”H
- Ships fully assembled

## Picture



## Applications

### Winery

- Crush Pad
- Bottling
- Cellar

### Food Processing

### Agriculture

### Dairy

### Shipping Ports

### Boat Docks

### Rail Yards

### Wind & Solar

## Technical Data

### Mechanical Interlock

*Current:* 30A & 60A

*Voltage:* 3Ø, 480V

*Frequency:* 60Hz

*Switch Horsepower:* 20HP(30A), 30HP(60A)

*Clock Position:* 7h (red)

*Material:* Glass Reinforced Polyester

*Temp Rating:* -40°F to 140°F

*Ingress Protection:* IP66/IP67/IP69  
NEMA type 3R, 4/4X, 12

*Safety:* Dual mechanical interlock  
On/Off LED  
OSHA Lockout/Tagout compliant

*Impact Protection:* IK10 (20J)

*Standards:* UL508 (non-fused)  
UL60947-4-1

