



LED PANEL LIGHT 600*1200 mm SIDE LIT

LUMIDEN LED PANEL LIGHT is suitable for lighting general area. It comes in Color Temperature options of 3000K to 6500 K with external power driver. Beam angle of 120 degree provides a wide coverage of the lighting area.

APPLICATIONS

Suitable for lighting up of offices, corridors, walkways and general areas.



BASIC SPECIFICATIONS	
LIGHT SOURCE	SMD 2835 LEDs
COLOR TEMPERATURE	3000 K ~ 6500 K
MATERIAL	ALUMINIUM +PMMA+PS
DIMENSIONS	595*1195*9 mm
WORKING TEMPERATURE	-20° C ~ + 50 ° C
INPUT VOLTAGE	AC 220~240 V, 50/60 HZ
LED POWER DRIVER	CONSTANT CURRENT MODE
WARRANTY	2 YEARS

MODEL NUMBER	COLOR OF FIXTURE	IP RATING FOR FIXTURE	COLOR TEMPERATURE	LUMENS	TYPE OF LIGHTING	UGR	CRI	BEAM ANGLE	W	CE/ROHS	PF
LMPNL1200-60CWF-S	WHITE	IP20	4000 K	5400	SIDE LIT, 2 SIDES	<19	>80	120 °	60	YES	>0.90
LMPNL1200-65CWF-S	WHITE	IP20	4000 K	5850	SIDE LIT, 2 SIDES	<19	>80	120 °	65	YES	>0.90
LMPNL1200-72CWF-S	WHITE	IP20	4000 K	6480	SIDE LIT, 2 SIDES	<19	>80	120 °	72	YES	>0.90
LMPNL1200-80CWF-S	WHITE	IP20	4000 K	7200	SIDE LIT, 2 SIDES	<19	>80	120 °	80	YES	>0.90