



LED PANEL LIGHT 40W IP RATED

LUMIDEN LED PANEL LIGHT is suitable for lighting general area and kitchen. It comes in Color Temperature options of 3000K to 6500 K with external power driver. Beam angle of 120 degree provides a wide coverage of the lighting area.

APPLICATIONS

Suitable for lighting up of Kitchens, canteens, pantry, offices, corridors, walkways and general



BASIC SPECIFICATIONS

LIGHT SOURCE	SMD 3030 LEDs EPISTAR
TYPE OF LIGHTING	BACK LIT
COLOR TEMPERATURE	3000 K ~ 6500 K
MATERIAL	ALUMINIUM + PS + WATERPROOF SILICON
DIMENSIONS	600 * 600 * 50 mm
WORKING TEMPERATURE	-20° C ~ + 45° C
INPUT VOLTAGE	AC 85 V ~ 265 V, 50/60 HZ
LED POWER DRIVER	IP 65 RATED CONSTANT CURRENT MODE
IK RATING	01
APPROVAL	EN 60598-2-2:2012 / EN 60598-1: 2015 EN55015:2013/A1:2015 EN61547:2009 EN61000-3-2:2014 / EN61000-3-3:2013

OLD MODEL NUMBER	NEW MODEL NJUMBER	COLOR	IP RATING FIXTURE	CCT	LUMENS	UGR	CRI	BEAM ANGLE	W	IP RATING LED DRIVER	EFFICIENCY	PF
LMPNL600-40WWF-IP5465	LMPNL6060-40WWF-IP5465	WHITE	IP54	3000~3500K	3600	<19	>80	120 °	40	IP 65	88%	>0.95
LMPNL600-40CWF-IP5465	LMPNL6060-40CWF-IP5465	WHITE	IP54	4000~4500K	3600	<19	>80	120 °	40	IP 65	88%	>0.95
LMPNL600-40PWF-IP5465	LMPNL6060-40PWF-IP5465	WHITE	IP54	6000~6500 K	3600	<19	>80	120 °	40	IP 65	88%	>0.95
LMPNL600-40WWF-IP65	LMPNL6060-40WWF-IP65	WHITE	IP65	3000~3500K	3600	<19	>80	120 °	40	IP 65	88%	>0.95
LMPNL600-40CWF-IP65	LMPNL6060-40CWF-IP65	WHITE	IP65	4000~4500K	3600	<19	>80	120 °	40	IP 65	88%	>0.95
LMPNL600-40PWF-IP65	LMPNL6060-40PWF-IP65	WHITE	IP65	6000~6500 K	3600	<19	>80	120 °	40	IP 65	88%	>0.95